

## Guardian Audio® ABS Series Speakers

Guardian Audio® ABS Series active speakers have a speakon output jack to connect and power a passive speaker. Pair an ABS10A, ABS12A or ABS15A active speaker with an ABS10, ABS12, or ABS15 passive speaker. The ABS10A also has a microphone input and can be used as a stand alone portable system. The ABS Series speakers use cast frame woofers and titanium diaphragm compression drivers



The internal crossover incorporates a lamp fuse for superior speaker protection. There are embedded M8 fly points for installing and a 1 3/8" stand mount to serve as main front of house system. One side of the cabinet is angled for use as a floor monitor.

<b>Active Model</b>	<b>Woofers</b>	<b>HF Driver</b>	<b>Power @ 8Ω / 4Ω</b>	<b>Sensitivity</b>	<b>Frequency Response</b>
ABS10A	10" Cast Frame	1.375"	150 / 250	97dB (1w/1m)	55Hz~20kHz
ABS12A	12" Cast Frame	1.375"	250 / 450	97dB (1w/1m)	45Hz~20kHz
ABS15A	15" Cast Frame	1.375"	250 / 450	99dB (1w/1m)	45Hz~20kHz

<b>Passive Model</b>	<b>Woofers</b>	<b>HF Driver</b>	<b>RMS Power</b>	<b>Sensitivity</b>	<b>Frequency Response</b>
ABS10	10" Cast Frame	1.375"	250 Watts	97dB (1w/1m)	55Hz~20kHz
ABS12	12" Cast Frame	1.375"	300 Watts	97dB (1w/1m)	45Hz~20kHz
ABS15	15" Cast Frame	1.375"	350 Watts	99dB (1w/1m)	45Hz~20kHz